



# KUT PLAST UW

## Admixture For Under Water Concrete

ADM – 16 - 0104

### DESCRIPTION

**KUT PLAST UW** is a blend of rheology control agents specially designed for use as underwater concreting admixture. Material is used in powder form.

### ADVANTAGES

- **Anti Washout:** Concrete produced with **KUT PLAST UW** is cohesive and demonstrates exceptional anti-washout properties underwater.
- **Minimal Clouding:** Does not cloud the diver's vision in water.
- **No Segregation:** Concrete remains homogeneous and does not segregate or bleed when placed.
- **Excellent Bond:** Because of thixotropic nature of concrete with **KUT PLAST UW**, it adheres readily to brick, concrete or steel surfaces without surface primers or bond coats under water.

### USES

Ports, harbors, quays and jetties, sea and driver defences. Repairs to precast units underwater, water retaining structures, dams, reservoirs spillways, columns, piles, concrete platforms.

### TECHNICAL DATA

- **Form** : Powder.
- **Suitability** : All portland cements including SRC.
- **Storage** : Protect from moisture. Store under shade.

### INSTRUCTIONS FOR USE

In order to obtain the best results, **KUT PLAST UW** must be used in specifically designed mixes for particular situations. **KUT PLAST UW** should be added along with cement and before addition of water for best results.

**Dosage** : 0.5 kg to 2.5kg per 100kg of cement.

Eg.: For a typical cement content of 350kg dosage of **KUT PLAST UW** can be between 1.175 to 8.75kg per cubic metre.

**Overdosing** : An overdose of 1.5 times the required amount will result in excessive retardation and final compressive strength of concrete will be affected.

### TECHNICAL SUPPORT

'**ASPEC**' provided technical support service on mix design, admixture selection, evaluation of trials please contact technical Dept in these cases.

### PACKAGING

**KUT PLAST UW** is supplied in 25kg bags.

### STORAGE

Shelf life is 12 months when stored in original packing in dry conditions at moderate temperatures. Open bag must be immediately closed back to airtight conditions.



Specialities Construction  
Chemicals Factory



Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait, Tel: +965 4565165 - 4565145 Fax: +965 4565135  
Email: technical@aspeckuwait.com

## HEALTH AND SAFETY

**KUT PLAST UW** is non toxic but is mildly alkaline. Gloves should worn during application. Splashes to the skin or eyes should be removed with clean water. In the event of prolonged irritation, seek medical advice.

### **FIRE :**

**KUT PLAST UW** is non-flammable but will burn with sooty flame in fire.

**ASPEC** endeavours to ensure that any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

**Distributor:**