



KUT CRETETARD TF

Topface Surface Retarder

CUR – 04 - 0104

DESCRIPTION

KUT CRETETARD TF is an aqueous spray applied topface surface retarder for concrete.

USES

KUT CRETETARD TF is used for application onto freshly placed horizontal concrete to produce an exposed aggregate surface excellent for receiving subsequent concrete or toppings.

APPLICATION

Compact the concrete using a wooden float, as steel tends to seal the surface. Then spray the **KUT CRETETARD TF** evenly at a rate of 3.5 m²/litre, utilizing a sprayer.

Protect the surface from rain, showers or frost during the curing period. Polythene sheeting can be used for this purpose.

Wash and brush off the retarded matrix as soon as possible after the mass of the concrete has hardened and certainly within 24 hours.

All equipment should be well washed with water.

TYPICAL PROPERTIES

Appearance	Greenish Blue Liquid
Specific Gravity @20° C	1.06
Flash Point	Non-flammable
Shelf Life (Sealed Container)	1 Year
Required Spray Rate	3.5m ² /litre

LIMITATIONS

Concrete admixtures can sometime interact with **KUT CRETETARD TF**. A trial area should be made if admixtures are to be utilised.

PACKAGING

KUT CRETETARD TF is supplied in 20 and 200 litre units.

PRECAUTIONS

Storage : Store at normal room temperature and do not allow the product to freeze.

HEALTH AND SAFETY

KUT CRETETARD TF is non-flammable and non-hazardous. Should contact with eyes result, wash well with water.



Specialities Construction
Chemicals Factory



Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait, Tel: +965 4565165 - 4565145 Fax: +965 4565135
Email: technical@aspeckuwait.com