



KUT DEGREASER C2

Solvent Based Cleaner & Degreaser

MIS – 15 - 0104

DESCRIPTION

KUT DEGREASER C2 is a high performance, non - corrosive solvent based cleaner and degreaser. It is based on a blend of organic solvents and a wetting agent which penetrate, lift and dissolve oil and grease contaminants, facilitating removal of grime by emulsifying with water used in subsequent washing or hosing down.

USES

- For easy removal of oil, grease and many other types of contamination from floors and machinery in factories, garages, workshops, warehouses and many other industrial facilities.
- For pre - treatment of contaminated floors prior to application of coatings, screeds and toppings.
- For cleaning of moulds and formwork prior to application of shutter paint and release agents.

ADVANTAGES

- Penetrating action lifts contamination quickly.
- Will not attack concrete wood or metal.
- No special equipment required.
- Effectively removes oil, grease and certain resinous compounds.

TYPICAL PROPERTIES

- **Specific Gravity** : 0.83 @ 20° C.
- **Colour** : Pale straw.

INSTRUCTIONS FOR USE

Preparation

It is recommended that where thick, heavy deposits of oil grease are present, they are removed by suitable mechanical means prior to treatment with **KUT DEGREASER C2**

Standard Treatment

Undiluted **KUT DEGREASER C2** should be liberally applied and scrubbed well into the affected areas. Following application, **KUT DEGREASER C2** should be left at least for at least 20 minutes to allow contamination to emulsify totally.

The softened contamination can then be washed away by hosing with water or steam whilst scrubbing with a stiff brush. The residue can then be channeled away to a drain or mopped up. For floors a final treatment with saw dust will speed up drying out.

Note : Care must be taken in meeting local health and safety regulations when disposing of the material.

Severe Contamination

For heavy deposits on large areas of concrete flooring, the use of a steam generator and a heavy duty floor scrubber fitted with a wire brush attachment will be advantageous.

In areas where extreme contamination exists and where a surface topping is to be applied, mechanical preparation is advisable.

Use as a dip

Small items such as contaminated tools can be immersed overnight in a suitable container containing **KUT DEGREASER C2**. Washing with clean water should then remove any residue.

PACKAGING

KUT DEGREASER C2 is supplied in 20 ltr. & 200 ltr. drums.



Specialities Construction
Chemicals Factory



PRECAUTIONS

Fire : KUT DEGREASE7R C2 contains flammable solvents. ensure adequate ventilation and do not use near a naked flame.

Storage : KUT DEGREASER C2 has a shelf life of 12 months if kept in dry and in the original un - opened pails. Protect from sunlight and away from direct heat. If stored at high temperatures and / or high humidity conditions the shelf life may be reduced to 4 to 6 months.

Flash Point : 48° C.

HEALTH & SAFETY

KUT DEGREASER C2 is flammable. Do not expose to naked flames or other sources of ignition. No smoking. Containers should be tightly sealed when not in use. In the event of fire, extinguish with CO₂ or foam.

Avoid inhalation of solvent vapours. Some people are sensitive to solvents. Gloves goggles and barrier creams should therefore be used. Ensure adequate ventilation. While working in closed areas, suitable breathing apparatus is recommended.

ASPEC endeavors to ensure that any information contained herein is true, accurate and represents our best knowledge and experience. No warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

Distributor: