



KUT SOFFIT PRIMER

High Build And Soffit Primer

PPC – 01 - 0104

DESCRIPTION

KUT SOFFIT PRIMER is a concentrated terpolymer acrylic white liquid emulsion modified to produce highbuild special primer for **KUT OVERHEAD MORTAR**.

It is single component emulsion to provide high grab adhesive properties for light weight overhead or vertical mortars.

USES

It is specially developed primer for use with **KUT OVERHEAD MORTAR**. It is used to provide excellent bond strength between high build repair mortars on overhead or vertical concrete.

It is used in both interior and exterior repair works. **KUT SOFFIT PRIMER** is recommended as a curing and surface protection sealer for **KUT OVERHEAD MORTAR** or cementitious site produced mortars. In such cases the **KUT SOFFIT PRIMER** will also act as a surfacing for receiving future coatings or tile finishing's.

ADVANTAGES

- **Quality:** Always fresh locally manufactured product.
- **Bonding:** Excellent quality bond for interior and exterior repair application.
- **Consistency:** High build single component product.
- **Simplified installation:** The repair mortars can be installed while the primer is still wet or tacky.

SURFACE PREPARATION

All, substrate should be, cleaned and free of dust, oil, paint, grease or contaminants, deleterious substances and disintegrated or loose concrete.

Excess laitance should be removed by mechanical means or acid etching and pressure water blasting.

APPLICATION

All steel reinforcement in the repair area must be fully exposed around its full circumference and cleaned from all loose scale and corrosion deposits.

The repair area must be thoroughly dampened with clean water and any excess water must be brushed off.

Brush **KUT SOFFIT PRIMER** into the surface using a stippling action to work the product into the surface and also the cavities or honeycombing.

Apply the **KUT OVERHEAD MORTAR** whilst the primer is still wet or tacky. Any surfaces that have dried out must be re-primed.

PACKAGING

KUT SOFFIT PRIMER is available in 5, 20 and 200kg drums.

Coverage: 2 to 3 m² per litre depending on the roughness of the concrete surface and the ambient temperature.

PRECAUTION

Cleaning: Equipment must be cleaned with water immediately after use. Mixes containing **KUT SOFFIT PRIMER** must not be emptied into drainage systems.

Protection: All works must be protected from rain, frost and exposure to strong sunlight until fully cured.

Storage: Shelf life is 12 months when stored in dry conditions at moderate temperature and humidity. Protect the product from frost.

Fire Resistance: **KUT SOFFIT PRIMER** is not flammable.

HEALTH AND SAFETY

KUT SOFFIT PRIMER is non toxic but is mildly alkaline. Gloves should be worn during application. Splashes to the skin or eyes should be removed with clean water. In the event of prolonged irritation, seek medical advice.



Specialities Construction
Chemicals Factory

Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait, Tel: +965 4565165 - 4565145 Fax: +965 4565135
Email: technical@aspeckuwait.com

