



KUT STABILISER

Masonry Stabiliser For All Friable Surfaces

PPC – 08 - 0104

DESCRIPTION

KUT STABILISER is pure acrylic liquid polymer modified with auxiliary agents to improve its deep penetration characteristics and sealing properties in existent porosities of concrete, sand lime bricks, cement mortars and concrete blocks.

USES

- **KUT STABILISER** is used as primer sealer on friable surfaces before the application of cement based coatings, paints and renders.
- It will stabilise, seal, strengthen, spalled, friable, unstable and weak surfaces of cement made materials and mortars.
- **KUT STABILISER** has exceptionally high wetting and penetrating properties to impregnate the capillary system in cementitious products also sand lime bricks producing a durable high performance barrier against the penetration of water and dampness.
- **KUT STABILISER** is recommended for use on industrial concrete floorings to provide an economical dust proof treatment.
- **KUT STABILISER** can be applied as an economical primer on absorbent cementitious surfaces, rendering and over sand lime bricks surfaces. When dry the **KUT STABILISER** gives an essentially colourless "sheen" appearance.

APPLICATION

Surfaces must be dry and free from oil and grease. Brush away loosely adhering material and dust before application. If lichen growth or mould is evident, surfaces may be treated with a suitable fungicidal wash followed by rinsing with water. Allow to dry before application of **KUT STABILISER**.

Apply liberally by brush roller or spray (some foaming can occur). A second coat may be required on very porous and exceptionally dusty surfaces. This should be applied after the first coat has dried. Drying time is 2 to 4 hours per coat depending on temperature and humidity.

Coverage will be vary considerably according to the method of use and the surface to which it is applied. The coverage is approximately 3 to 6m² per kg. When lichen growth, mould or efflorescence are evident, the surface may be treated with suitable fungicidal or acid cleaner followed by rinsing. In case of doubt, consult our Sales & Technical Dept.

PACKAGING

KUT STABILISER is available in 5, 20 and 200 kgs containers.

PRECAUTION

Cleaning : All equipment must be cleaned with water immediately after use. Mixes containing this product must not be emptied into drainage systems.

Storage : **KUT STABILISER** has a shelf life of 12 months when kept in a dry store at moderate temperature above 5⁰ C. The product must be protected from frost.

Fire resistance : The product is not flammable.

HEALTH AND SAFETY

The product is non toxic but care should be taken to avoid splashes In the eyes and inhaling the vapours. Avoid prolonged contact with the skin. It is harmful if taken internally. Splashes to the skin or eyes should be removed with clean water. In the event of prolonged irritation, seek medical advice.



Specialities Construction
Chemicals Factory

Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait, Tel: +965 4565165 - 4565145 Fax: +965 4565135
Email: technical@aspeckuwait.com

